

INSTRUCTIONS ADJUSTABLE-ANTI-PILFERAGE GUARD INSTALLATION, FOR NATIONAL VENDORS CROWN SEVENTY TWO® , SERIES EPM-72, AND GOLDEN FURNITURE LINE EPM-72, ELECTRIC PASTRY MERCHANDISERS

This Adjustable Anti-Pilferage Guard Kit, part number 139-6039 may be installed in any National Vendors, Crown Seventy Two®, Series EPM-72 and Golden Furniture Line EPM-72, Electric Pastry Merchandisers. This Kit consists of the following parts:

Part Number	Description	Quantity
139-6047	Guard Assembly, Adjustable Anti-Pilferage	1
9900-187	Screw, No. 8-32 x 3/8" RHS Self-Tapping	4
139-6040	Instructions, Installation * * *	1

Carefully and thoroughly read these instructions before doing the actual work of installing the Kit, and follow the procedures in the order given.

I. Installation and Adjustment of the Anti-Pilferage Guard.

A. TO INSTALL THE ANTI-PILFERAGE GUARD:

1. Disconnect the Merchandiser Service Cord from wall receptacle.
2. Open the Cabinet Door and rotate Delivery Mechanism out to expose the Right Sidewall.
3. Remove Reset Motor Cover by removing three No.8-32 screws.
4. If the Merchandiser contains a Non-Adjustable Anti-Pilferage Guard, remove it.

NOTE

There are numerous screws through each Sidewall adjacent to those holding the Anti-Pilferage Guard. Observe carefully to determine the proper screws to be removed.

5. Before installing the Adjustable Anti-Pilferage Guard, determine if the Adjustable portion of the Guard is set in its approximate mid position. If not loosen, with a wrench, the five No.8-32 nuts with lockwashers across the bottom rear portion of the Guard and set the Guard to its mid position. Tighten the nuts being careful to keep the bottom edge of the Guard parallel to the top edge of the Guard Channel

6. Slide the Anti-Pilferage Guard up into the Delivery Pan. See Figure for orientation of the Guard.

7. Hold Anti-Pilferage Guard in position and install two of the self-tapping screws furnished, in the two vacant holes adjacent to the Reset Motor in the Right Sidewall, so that the top one extends into the upper formed portion of the Guard and the bottom screw threads into the hole in the Angle Bracket of the Anti-Pilferage Guard.

8. Rotate the Delivery Mechanism completely out of the Cabinet. Grasp the Guard and hold it level.

9. Install two self-tapping screws in the available holes in the Left Sidewall.

10. Rotate Delivery Mechanism back into Cabinet.

B. TO ADJUST THE ANTI-PILFERAGE GUARD:

1. Place the product having the maximum height in the Delivery pan in the position it would be in if it had been delivered.

2. Slide the product up and under the Anti-Pilferage Guard. If the product slides up without interference note the amount by which it clears the Guard. If the amount of clearance is about 1/8 inch proceed to step B-7. If the product will not slide up due to interference or if the clearance is more than 1/8 inches note the amount of interference or clearance.

3. Rotate the Delivery Mechanism out of the Cabinet.

4. Remove the Anti-Pilferage Guard from the Merchandiser by removing the four No.8-32 self-tapping screws installed in steps A-7 and A-9. Carefully move the Guard forward out of the Delivery Pan.

NOTE

There are numerous screws through each Sidewall adjacent to those holding the Anti-Pilferage Guard; Observe carefully to determine the proper screws to be removed.

5. Loosen, with a wrench, the five No.8-32 nuts with lockwashers across the rear bottom of the Anti-Pilferage Guard. Adjust the lower portion of the Anti-Pilferage Guard to allow about 1/8 inch of clearance between the bottom surface of the Anti-Pilferage Guard Assembly and the top of the thickest product to be vended. Be sure to adjust the Guard so that its bottom will be parallel to surface of the Delivery Tray and tighten the five nuts.
6. Install the Anti-Pilferage Guard, using the four No.8-32 screws removed in Step B-4.
7. Install the Reset Motor Cover using three No.8-32 screws removed in Step A-3.
8. Rotate the Delivery Mechanism back into the Cabinet.
9. Close and lock the Door.
10. Connect the Merchandiser Service Cord to a wall receptacle.
11. Check to determine if the Anti-Pilferage Guard has been set to provide adequate clearance by test vending at least five of the items from the Column having the thickest product.
12. If the Anti-Pilferage Guard is not set correctly repeat Steps B-1 through B-11. If the Anti-Pilferage Guard is set correctly place the Merchandiser in service.

