

# Vend Test Database

Date: 06/12/2003  
 \*Size: 16.9 OZ  
 Release 3  
 Level:

\*Model: 440 PRE SERIES 90  
 \*Type: PET

ECN #: 000925  
 Test #: 2003-1165-01  
 Country: USA  
 \*Description: CHIPPEWA SPRING WATER

Pkg. Dia. (inches): 2.56  
 Pkg. Dia. (mm): 65.02

Pkg. Ht. (inches): 8.01  
 Pkg. Ht. (mm): 203.45

New  
 Revised

Instructions:

**Wide Column Setup Deep: 1**

| Qty | Part Number    | Description                   |
|-----|----------------|-------------------------------|
| 4   | 801,804,96x.x1 | flat black shim (2 each side) |
| 1   | 801,806,99x.x1 | vending cam, white            |
|     |                |                               |
|     |                |                               |
|     |                |                               |
|     |                |                               |
|     |                |                               |
|     |                |                               |
|     |                |                               |
|     |                |                               |
|     |                |                               |
|     |                |                               |
|     |                |                               |
|     |                |                               |
|     |                |                               |
|     |                |                               |



Notes:

Cam set in hole #: 1                      Rear Spacer set in hole #: 14  
 Load Package: caps to the back

**Narrow Column Setup Deep: 1**

| Qty | Part Number    | Description        |
|-----|----------------|--------------------|
|     |                | no shims required  |
| 1   | 267,012,30x.x3 | rod & spring assy. |
|     |                |                    |
|     |                |                    |
|     |                |                    |
|     |                |                    |
|     |                |                    |
|     |                |                    |
|     |                |                    |
|     |                |                    |
|     |                |                    |
|     |                |                    |
|     |                |                    |
|     |                |                    |
|     |                |                    |
|     |                |                    |

Notes: Place rod in hole "B" of rotor. No shims required

Cam set in hole #: 4                      Rear Spacer set in hole #: 14  
 Load Package: caps to the back

|                                 |                            |
|---------------------------------|----------------------------|
| Discharge Member: standard      | Wide Column Capacity: 40   |
| Closure Strip: standard         | Narrow Column Capacity: 21 |
| Can Chute Accessories: standard | Total Capacity: 244        |