INSTALLATION INSTRUCTIONS FOR INSTALLING A TEA DISPENSER REPLACEMENT KIT IN A NATIONAL VENDORS®, CROWN SEVENTY TWO®, SERIES OR GOLDEN FURNITURE LINE HBM-614 AND HBM-618 HOT BEVERAGE MERCHANDISER

These instructions cover the procedure for installing a Tea Dispenser Replacement Kit in a Crown Seventy Two, Series or Golden Furniture Line HBM-614 and HBM-618 Hot Beverage Merchandiser.

Read these instructions carefully and thoroughly before installing the Kit. Retain these instructions for part number and installation information.

These instructions apply to two Kits. Kit, Part Number 613-7151 applies ONLY to the HBM-614 Merchandiser and contains the following parts:

Part Number	Description	Quantity
613-7144 613-7148 9900-163 618-7001 112-7057 618-7002	Tea Dispenser Harness Tea Dispenser Assembly No.10-32 x 5/8 RHS S/T Screw Tea Mixing Bowl Knurled Head Screw	1 1 2 1 2
613-7001 613-7137 613-7138	Tea Mixing Bowl Vent Tea Dispenser Elbow Tea Water Valve to Tea Mixing Bowl Tube Tea Mixing Bowl to Mixing Bowl Tube	1 1 1
613-7161 613-7173 610-7231 613-7146 613-7152	Mixing Bowl Exhaust Hose Tea Exhaust Hose Vinyl Cap Tea Canister Assembly Installation Instructions * * *	1 1 2 1

Kit, Part Number 618-7023, applies ONLY to the HBM-618 Merchandiser and contains the following parts:

		- P Parto
613-7144	Tea Dispenser Harness	4
613-7148	Tea Dispenser Assembly	1
9900-204	No.8-32 x 5/8 RHS S/T Screw	1
618-7001	Tea Mixing Bowl	2
112-7057	Knurled Head Screw	1
618-7002		2
613-7001	Tea Mixing Bowl Vent	1
618-7019	Tea Dispenser Elbow	1
010-7019	Tea Water Valve to Tea Mixing	1
_	Bowl Tube	•
618-7020	Tea Mixing Bowl to Mixing	4
	Bowl Tube	
618-7025	Tea Exhaust Hose	
610-7231		1
613-7146	Vinyl Cap	2
	Tea Canister Assembly	1
6 13 -7152	Installation Instructions	,
	* * *	'

SPECIAL TOOLS REQUIRED (HBM-618 only) Drill

1/64 dia. Drill Bit

TO INSTALL THE KIT

A. PARTS REMOVAL

- 1. Unlock and open the Cabinet Door.
- 2. Move the Main Switch in the Merchandiser to the OFF position.
- 3. Remove the Tea Dispenser Exhaust Hose from the Merchandiser. See Figure 1 for HBM-614 Merchandisers and Figure 1A for HBM-618 Merchandisers.

NOTE

Step 4 applies only to the HBM-614 Merchandiser.

- 4. Remove the Mixing Bowl Exhaust Hose from the Merchandiser. See Figure 1.
- 5. Remove the Tea Dispenser to Mixing Bowl Tube from the Merchandiser. See Figure 1 or Figure 1A.

NOTE

Step 6 applies only to the HBM-614 Merchandiser.

- 6. Remove the Tea Dispenser Elbow (if equipped) from the bottom of the Tea Dispenser. See Figure 1.
- 7. Remove two Sidewall Thumb Screws and the Water Valve Cover Assembly from the Merchandiser. See Figure 1 or Figure 1A.
- 8. Remove the Tea Water Valve to Mixing Funnel Tube from the Merchandiser. See Figure 1 or Figure 1A.
- 9. Remove the Left Splash Panel Assembly from the Merchandiser. See Figure 2.
- 10. Disconnect the Tea Dispenser Harness from the Dry Ingredients Harness. See Figure 2.
- 11. Remove three No.10-32 x 5/8 Round Head Self Tapping Screws and the Tea Dispenser Assembly and Tea Jar from the Merchandiser. See Figure 1 or Figure 1A.

NOTE

Step 12 applies only to an HBM-614 Merchandiser.

Printed in U.S.A.




FIGURE 1




FIGURE 1A

3 of 8

. . . .




FIGURE 2

12. Remove a No.10-32 x 5/8 Round Head Self Tapping Screw from the upper part of the Dry Ingredients Shelf which was behind the Tea Dispenser Assembly. See Figure 1.

NOTE

Step 13 applies only to an HBM-618 Merchandiser.

- Remove and retain the Vinyl Cap from the Exhaust Housing in the Merchandiser. See Figure
- B. INSTALLATION OF THE KIT

NOTE

Step 1 applies only to the HBM-618 Merchandiser.

- 1. Using page 8 as a template, align the two top holes of the template with the two existing mounting holes on the Right Sidewall; then drill two 9/64 inch diameter holes where indicated. See Figure 3A.
- Connect the Tea Dispenser Harness, Part Number 613-7144, included in the Kit, to the receptacle marked "T" on the Dry Ingredients Harness. See

- Figure 2. On HBM-614 Merchandisers, run the other end of the Tea Dispenser Harness through the hole in the Dry Ingredients Shelf as shown in Figure 3. On HBM-618 Merchandisers, run the other end of the Tea Dispenser Harness around the Dry Ingredients Shelf as shown in Figure 3A.
- 3. Install the Left Splash Panel Assembly in the Merchandiser. See Figure 2.
- 4. Install the Tea Dispenser Assembly, Part Number 613-7148, included in the Kit, in the Merchandiser and attach with two No.10-32 x 5/8 Round Head Self Tapping Screws, Part Number 9900-163, included in Kit 613-7151 or two No.8-32 x 5/8 Round Head Self Tapping Screws, Part Number 9900-204, included in Kit 618-7023. See Figure 3 for HBM-614 Merchandisers or Figure 3A for HBM-618 Merchandisers.
- 5. Connect the free end of the Tea Dispenser Harness to the receptacle on the Tea Dispenser Assembly. See Figure 3 or Figure 3A.
- 6. Attach the Tea Mixing Bowl, Part number 618-7001, included in the Kit, to the Tea Dispenser Assembly using two Knurled Head Screws, Part Number 112-7057, included in the Kit. See Figure 3 or Figure 3A.




FIGURE 3




FIGURE 3A

- 7. Fit the Tea Mixing Bowl Vent, Part Number 618-7002, included in the Kit, on top of the Tea Mixing Bowl. See Figure 3 or Figure 3A.
- 8. Install the Tea Dispenser Elbow, Part Number 613-7001, included in the Kit, on the Tea Mixing Bowl. See Figure 3 or Figure 3A.

NOTE

Steps 9 through 13 apply only to the HBM-614 Merchandiser.

- 9. Connect one end of the 10 inch Tea Water Valve to Tea Mixing Bowl Tube, Part Number 613-7137, included in the Kit, to the Tea Dispenser Elbow on the Tea Mixing Bowl and the other end of the Tube to the Tea Water Valve. See Figure 3.
- 10. Connect one end of the 8 3/4 inch Tea Mixing Bowl to Mixing Bowl Tube, Part Number 613-7138, included in the Kit, to the bottom of the Tea Mixing Bowl and the other end of the Tube to the Mixing Bowl. See Figure 3.
- 11. Connect one end of the shorter Mixing Bowl Exhaust Hose, Part Number 613-7161, included in the Kit, to the left side of the Tea Mixing Bowl Vent and the other end of the Mixing Bowl Exhaust Hose to the top of the Mixing Bowl. See Figure 3.
- 12. Connect one end of the longer Tea Exhaust Hose, Part Number 613-7173, included in the Kit, to the top of the Tea Mixing Bowl Vent and the other end of the Tea Exhaust Hose to the Exhaust Housing. See Figure 3.
- 13. Place the two Vinyl Caps, Part Number 610-7231, included in the Kit, over the openings in the Exhaust Housing and Tea Mixing Bowl Vent. See Figure 3.

NOTE

Steps 14 through 18 apply only to the HBM-618 Merchandiser.

- 14. Connect one end of the 11 3/4 inch Tea Water Valve to Tea Mixing Bowl Tube, Part Number 618-7019, included in the Kit, to the Tea Dispenser Elbow on the Tea Mixing Bowl and the other end of the Tube to the Tea Water Valve. See Figure 3A.
- 15. Connect one end of the 12 1/2 inch Tea Mixing Bowl to Mixing Bowl Tube, Part Number 618-7020, included in the Kit, to the bottom of the Tea Mixing Bowl and the other end of the Tube to the Mixing Bowl. See Figure 3A.
- 16. Place the Vinyl Cap, removed in Step A-13, over the opening on the right side of the Coffee Mixing Bowl Vent. See Figure 3A.
- 17. Connect one end of the Tea Exhaust Hose, Part Number 618-7025, included in the Kit, to the left side of the Tea Mixing Bowl Vent and the end of the Tea Exhaust Hose to the Exhaust Housing. See Figure 3A.
- 18. Place the two Vinyl Caps, Part Number 610-7231, included in the Kit, over the openings on the Tea Mixing Bowl Vent. See Figure 3A.
- 19. Place the Tea Canister Assembly, Part Number 613-7146, included in the Kit, on the Tea Dispenser Assembly making sure the Canister Hanger on the rear of the Tea Canister Assembly hooks on the Canister Mounting Bracket Assembly and that the roll pin on the Tea Dispenser Motor fits in the Coupling on the Tea Auger Assembly. See Figure 3 or Figure 3A.
- 20. Remove the Lid from the Tea Canister Assembly and fill the Canister with Tea or De-Caffeinated Coffee. Place the Lid back on the Tea Canister Assembly.

C. CHECKS AND ADJUSTMENTS

- Follow the procedures in the Set-Up Instructions for testing and adjusting the Tea Powder Throw or De-Caffeinated Coffee Throw.
- 2. Close and lock the Cabinet Door.

R L

