

# Vend Test Database

**Date:** 07/21/98  
**\*Size:** 8.4 OZ  
**Release Level:**

**\*Model:** 600E SERIES 90  
**\*Type:** CAN

**ECN #:** 98-127-02  
**Test #:** 98-609-06  
**Country:** USA  
**\*Description:** RED DEVIL

**Pkg. Dia. (inches):** 2.08  
**Pkg. Dia. (mm):** 52.8

**Pkg. Ht. (inches):** 5.19  
**Pkg. Ht. (mm):** 131.8

New  
 Revised

Instructions:

**Wide Column Setup Deep: n/a**

| Qty | Part Number | Description |
|-----|-------------|-------------|
|     |             |             |
|     |             |             |
|     |             |             |
|     |             |             |
|     |             |             |
|     |             |             |
|     |             |             |
|     |             |             |
|     |             |             |
|     |             |             |
|     |             |             |
|     |             |             |
|     |             |             |
|     |             |             |
|     |             |             |
|     |             |             |
|     |             |             |
|     |             |             |



**Notes:** Will Not Vend

**Cam set in hole #:**                           **Rear Spacer set in hole #:**  
**Load Package:**

**Narrow Column Setup Deep: 3**

| Qty | Part Number    | Description                               |
|-----|----------------|---|
| 1   | 609,070,62x.x3 | Can stop shim - extended lip, right       |
| 1   | 610,070,05x.x3 | Shim angle (attach to top of shim), right |
| 1   | 610,011,50x.x3 | Assy. column wall, right                  |
| 1   | 609,070,63x.x3 | filler shim, left                         |
| 1   | 432,070,17x.x3 | sold out paddle, narrow                   |
| 2   | 800,503,83x.x1 | rod & spring assy.                        |
| 2   | 801,903,24x.x1 | white tube                                |
|     |                |   |
|     |                |   |
|     |                |   |
|     |                |   |
|     |                |   |

**Notes:** Place rod with white tube in hole "A" of rotor. Place rod with white tube in hole "C" of rotor.

**Cam set in hole #:** 1                           **Rear Spacer set in hole #:** 16  
**Load Package:** Tops to the back.

|                               |            |                                |     |
|-------------------------------|------------|--------------------------------|-----|
| <b>Discharge Member:</b>      | large port | <b>Wide Column Capacity:</b>   | 0   |
| <b>Closure Strip:</b>         | large port | <b>Narrow Column Capacity:</b> | 69  |
| <b>Can Chute Accessories:</b> | large port | <b>Total Capacity:</b>         | 552 |