

# Technical Bulletin

Bulletin Number: 232 Revision Number: R-02

Release Date: January 7, 1981 Revision Date: September 9, 1999

## OBSOLETE See TB 261

**MODELS:** DNCB ADAPTABLES AND DUAL ADAPTABLES ONLY (except Magnums, Circular Magnums, and Circular Coke)

**SUBJECT:** Strike Plate Installation for Inner Door Lock

**ORDER AS:** B/M267,010,100.04 – Accy. Lock Kit Inner Door

**KIT CONSISTS OF:**

*1 – 801,501,540.01	Inner Door Locks with 2 Keys
1 – A267,010,010.03	Strike Plate
2 – 900,600,230.02	Screws #8x1/2"
1 – 801,503,140.01	Cam (6-601-Z)
1 – A360,010,160.03	Lock Hole Plate – Inner Door (Install on outside of inner door)
4 – 901,100,500.01	Rivets – 1/8" (Install on outside of inner door)

**\*IF THERE ARE NO HOLES IN FLANGE OF MAIN DOOR AND NO HOLE IN THE ACCESS DOOR**

KIT WILL CONSIST OF:

*1 – B/M267,010,100.04	Accy. Lock Kit Inner Door
1 – A267,050,071.53	Access Door – Sub Assembly

**DO THIS:**

- See figure 1 and figure 2.
- Locate and drill two (2) 7/32" holes through door flange.

NOTE: \*If you have Inner Door Locks in stock, order only parts needed.

\* A limited number of DNCB Models were manufactured less Flange Holes, less Hole in Access Door.

