

# Technical Bulletin

Bulletin Number: 453 Revision Number: R-15

Release Date: October 16, 1992 Revision Date: October 1, 1999

SUBJECT: MISCELLANEOUS WORLDWIDE PLASTIC BOTTLE SHIMMING IN SHIMLESS STACK SERIES 90 VENDERS


MODELS AFFECTED: All Shimless Stack Series 90 Venders.

**REASON:** To provide the shimming and set-up of various plastic bottles used Worldwide.

#### **BULLETIN INDEX**

A)	Package Shape Illustrations	Page 2
B)	Package Dimensions	Pages 3 and 4
C)	Drawings or Illustrations	
D)	Shimming and Set-Up Chart	Pages A1 through A4
E)	Individual Column Set-Up & Shimming	Pages B1 through B12

# **Package Shapes**



9


# **Package Dimensions**

D 1.1	Package	Country/	G.		leight	Diameter	
Description Straight Bottle	Size 500 ml	Township Africa	Shape 1	8.57"	nes (mm) (217.7)		es (mm) (64.8)
							` ′
Coca-Cola Contour	500 ml	Australia	2	8.86"		2.66"	(67.6)
Coca-Cola Contour	600 ml	Australia	2	9.53"		2.86"	(72.6)
Jeema Water	500 ml	Australia	9	8.23"	, ,	2.54"	(64.5)
Mount Franklin	500 ml	Australia	1	7.16"	(181.9)		(71.1)
Multi-Brand	600 ml	Australia	4	9.41"	(239)	2.86"	(72.6)
Pepsi (Wide Mouth)	500 ml	Australia	1	9.24"	(234.7)		(65.3)
Powerade	500 ml	Australia	7	7.47"	(189.7)	2.72"	(69)
Sprite	600 ml	Australia	2	9.54"	(242.3)	2.85"	(72.4)
Straight Bottle	500 ml	Australia	4	8.69"	(220.7)	2.66"	(67.6)
Naya Water	12 oz.	Canada	3	6.53"	(165.9)	2.46"	(62.5)
Naya Water	16.9 oz.	Canada	3	8.56"	(217.4)	2.45"	(62.2)
Contrex Water	50 cl	France	9	8.5"	(215.9)	2.45"	(62.2)
Evian Water	50 cl	France	3	8.82"	(224)	2.45"	(62.2)
Plastic Bottle	500 ml	Iceland	1	7.82"	(198.6)	2.70"	(68.6)
Neviot Mineral Water	50 cl	Israel	3	7.82"	(198.6)	2.61"	(66.3)
Carbonated Water	500 ml	Italy	1	8.33"	(211.6)	2.70"	(68.6)
Coca-Cola Contour	500 ml	Italy	2	9.24"	(234.7)	2.59"	(65.8)
Non-Carbonated Water	500 ml	Italy	1	8.21"	(208.5)	2.67"	(67.8)
Pureza Aga Water	355 ml	Mexico	3	7.10"	(180.3)	2.26"	(57.4)
Coca-Cola Contour	500 ml	Norway	2	9.08"	(230.6)	2.53"	(64.3)
Coca-Cola Contour	500 ml	Spain	2	9.13"	(231.9)	2.59"	(65.8)
Coca-Cola Contour	500 ml	United Kingdom	2	8.93"	(226.8)	2.57"	(65.3)
Vittel Water (Square Bottle)	17 oz.	United Kingdom	3	7.52"	(191)	2.44"	(62)
Avalon Water	12 oz.	United States	3	6.53"	(165.9)	2.46"	(62.5)
Avalon Water	12 oz.	United States	3	7.37"	(187.2)	2.31"	(58.7)
Avalon Water	16.9 oz.	United States	3	8.52"	(216.4)	2.45"	(62.2)
Avalon Water (Sport Cap)	16.9 oz.	United States		8.79"	(223.3)	2.58"	(65.5)
Balsams Spring Water	16 oz.	United States	6	7.25"	(184.2)	2.64"	(67)
Castle Springs Water	12 oz.	United States	3	7.08"	(179.8)	2.32"	(58.9)
Castle Springs Water	16.9 oz.	United States	3	7.97"	(202.4)		(66.8)
Coca-Cola Contour	20 oz.	United States	2	9.03"	(229.4)		(72.6)
Crystal Light	16 oz.	United States	3	7.94"	(201.7)		(64.8)
Evian Water	330ml/11.2oz.	United States	3	6.35"	(161.3)		(60.7)
					(121.0)		(==./)

Description	Package Size	Country/ Township	Shape		leight nes (mm)		meter es (mm)
Evian (On Ice)	330 ml	USA	3	6.63"	(168.4)	2.45"	(62.2)
Evian Water	16.9 oz	United States	3	8.74"	(222)	2.42"	(61.5)
Evian (On Ice)	500 ml	United States	3	8.45"	(214.6)	2.48"	(63)
Glen Falls Water	16 oz.	United States	3	8.10"	(205.7)	2.49"	(63.2)
Grayson Water	16.9 oz.	United States	3	9.14"	(232.2)	2.50"	(63.5)
LaCroix Water	16.9 oz.	United States	3	8.05"	(204.5)	2.59"	(65.8)
Mistic Sport	20 oz.	United States	3	9.24"	(234.7)	2.81"	(71.4)
Mountain Valley Water	12 oz.	United States	3	7.26"	(184.4)	2.31"	(58.7)
Mountain Valley Water	16.9 oz.	United States	3	8.15"	(207)	2.60"	(66)
Naya Water	16.9 oz. (500 ml)	United States	3	8.56"	(217.4)	2.45"	(64.8)
Pepsi (4 section bottom)	12 oz.	United States	1	6.31"	(160.3)	2.64"	(67)
Pepsi Fastbreak	20 oz.	Birmingham, AL	1	9.08"	(230.6)	2.67"	(67.8)
Poland Springs Water	12 oz.	United States	3	7.07"	(179.6)	2.32"	(58.9)
Poland Springs Water	16.9 oz.	United States	3	7.94"	(201.7)	2.63"	(66.8)
Poland Springs Water	490 ml	United States	3	7.82"	(198.6)	2.55"	(64.8)
Zephyrhills Spring Water	16.9 oz.	United States	3	7.82"	(198.6)	2.55"	(64.8)

- 1. Where the symbols \*, + and @ are used refer to the following: (Use plastic tubes only where called out.)
  - \* Where the symbol \* appears on the shim chart, place the 10-3/4" long (9/32"ID, 3/8"OD) yellow plastic tube over the rod.
  - + Where the symbol + appears on the shim chart, place the 10-3/4" long (9/32"ID, 7/16"OD) red plastic tube over the rod.
  - @ Where the symbol @ appears on the shim chart, place the 10-3/4" long (9/32"ID, 17/32"OD) white plastic tube over the rod.
- 2. Where **REAR A/FRONT C** appears on the shim chart, this means the rod is installed (spring end first) in hole "A" at the rear of the rotor and the front end of the same rod is installed in hole "C".


#### **PARTS ILLUSTRATIONS**




801,804,96x.x1



Grey Shim 801,805,12x.x1



W/A Shim Left 443,010,60x.x3



W/A Shim Right 443,010,70x.x3


### INSTALLATION OF COLUMN WALL KIT

#### **NARROW COLUMNS**

- 1. Unplug the vender.
- 2. Remove any existing shims.
- 3. Move the rear spacers to the rear of each column.
- 4. Remove the center tie bar.
- 5. Take the narrow column wall kit and locate the "clips" which are welded to the back side of the wall. See figure below.
- 6. Place the narrow kit wall in the column so the "clips" are towards the right column wall.
- 7. Align the "clips" with the existing slots in the right side stack wall.


  Note: There are two (2) upper and two (2) lower slots in each stack wall.

  Use the lower slots at each location.
- 8. Press the wall in position an ensure the "clips" are seated in the slots.
- 9. Set the rear spacer in the proper position.
- 10. Reinstall the center tie bar removed in step 4.
- 11. If using a Pre-Series 90 T-Model vender, go to step 14.
- 12. Remove existing sold out paddle.
- 13. Install new sold out paddle (part #432,070,17x.x3) in Series 90 venders.
- 14. Set the cams in the proper position.
- 15. Load the product and test for proper vending.



Narrow Right Column Wall

#### **DIVIDER ANGLE INSTALLATION:**



## INSTALLATION OF COLUMN WALL KIT

#### WIDE COLUMNS


- 1. Unplug the vender.
- 2. Move the rear spacers to the rear of each column.
- 3. Identify the right and left parts for proper placement.
  - A. See Figures 1 and 2 below for identification.

Note: The dimension from the bottom of the part to the first clip is 6-1/8" (155.6mm) on a right side part and is shown to assist in part identification. The dimension on the left hand part from the bottom of the part to the first clip is 8-1/8" (206.4mm).

- 4. Take the right kit and locate the "clips" which are welded to the back side of the part.
- 5. Place the right kit in the column so the "clips" are towards the right column wall.
- 6. Align the "clips" with the existing slots in the right stack wall.

  Note: There are two (2) upper and two (2) lower slots in each stack wall.

  For the right kit use the lower slots at each location.
- 7. Push the wall in position to secure (clips in slots).
- 8. Install the left kit wall by repeating steps 4, 5, 6 and 7 using the upper slots at each location.
- 9. Set the rear spacer in the proper position.
- 10. Set the cams in the proper position.
- 11. Load the product and test for proper vending.



# **EXTENDED DISCHARGE MEMBER INSTRUCTIONS**

- 1. Remove the nuts and bolts securing the discharge member to the delivery port.
- 2. Remove existing discharge member.
- 3. Install extended discharge member so holes B & D (see figure 3A or 3B) line up with the back holes in the delivery port (see figure 4).
- 4. Figure 4 shows what the set-up should now look like.
- 5. Secure with the nuts and bolts removed in step 1.




Figure 3A
Extended Discharge Member Narrow
493,051,10x.x4




Figure 3B
Extended Discharge Member Wide

491,051,70x.x4 - for wide Coke Landscape, Pepsi Magnum Circular, &
Generic Circular Venders

491,051,90x.x4 - for All Full Length Sign Flat & Display Venders




Figure 4

Use This Chart To "Set-Up" And "Shim" The "Shimless Stack" Vender. Series 90, Beginning 2/N 0001-3162AO & Up (Except Run Numbers 3164AO, 3166AO, And 3167AO). Pre-Series 90, Beginning S/N 0001-3098AN To 0001-3162AO (Except 1954-3161AO To 2003-3161AO & 2656-3161AO To 2750-3161AO) Includes Production Runs 3164AO, 3166AO, And 3167AO)

#### PLASTIC BOTTLES

			Wide Columns				All Columns Narrow Columns						
PACKAGE DESCRIPTION & VENDERS APPROVED	COUNTRY	SEE PAGE(S)	LOADING DEPTH	PARTS PER COLUMN	CAM SETTING	CAM(S) REQUIRED	REAR SPACER LOCATION	LOADING DEPTH	PARTS REQ'D PER COLUMN	ROD IN	ROD IN	CAM SETTING	OTHER PARTS
500 ml PET Straight Bottle in Models 368 & 440	Africa	2, 3, 5, & B1	1	4 flat black shims	2 notches	blue/gold	Hole #16	1	no shims required	-	-	#4	none
500 ml PET Contour Coke Bottle in Models 276, 360, & 440	Australia	2, 3, 5, & B1	1	hem angles and channel	2 notches	blue/gold	Hole #16	1	1 grey shim right	-	-	#4	none
600 ml PET Contour Coke, 600 ml PET Multi-Brand, 600 ml PET Sprite Bottles in Model 440	Australia	2, 3, & B1	-	will not vend at this time	-	-	Hole #18	1	1 rotor, milled	-	-	#4	none
.5 Liter PET Jeema Water Bottle in Model 440	Australia	2, 3, 5, 6, & B2	1	2 flat black shims	2 notches	blue/gold	Hole #15	1	0	-	-	#4	divider angle
500 ml PET "Mount Franklin" Bottle in Models 276, 368, & 440	Australia	2, 3, & B2	1	1 milled oscillator	2 notches	blue/gold	Hole #12	1	0	-	-	#4	none
500 ml Pepsi "Wide Mouth" (The Slam) Bottle in Model 368	Australia	2, 3, & B2	1	0	2 notches	blue/gold	Hole #17	1	no shims required	-	-	#4	none
500 ml PET Powerade Bottle in Models 368 & 440	Australia	2, 3, B2, & B3	1	1 milled oscillator	2 notches	blue/gold	Hole #13	1	1 milled rotor	-	-	#4	none
500 ml PET Straight Bottle in Models 276 & 440	Australia	2, 3, 5, 6, & B3	1	right & left w/a shim	2 notches	blue/gold	Hole #15	1	w/a wall right	Rear A Front C	-	#4	divider angle
16.9 oz. Naya Water, 16.9 oz. Avalon in Models 440 & 368	Canada United States	2, 3, 5, & B3	1	4 flat black shims	2 notches	blue/gold	Hole #16	1	1 grey shim right	В	-	#4	none
50 cl Contrex Water Plastic Bottle in Model 368	France	2, 3, 5, B3, & B4	1	2 flat black shims	2 notches	blue/gold	Hole #16	1	1 flat shim right	A+	-	#4	none

			Wide Columns				_	All Columns Narrow Columns						
PACKAGE DESCRIPTION & VENDERS APPROVED	COUNTRY	SEE PAGE(S)	LOADING DEPTH	PARTS PER COLUMN	CAM SETTING	CAM(S) REQUIR ED		REAR SPACER LOCATION	LOADING DEPTH	PARTS REQ'D PER COLUMN	ROD IN	ROD IN	CAM SETTING	OTHER PARTS
50 cl PET Evian Water Bottle in Model 368	France	2, 3, 5, & B4	1	4 flat black shims	2 notches	blue/gold		Hole #16	1	1 grey shim right	В	-	#4	none
500 ml PET Bottle in Models 360 & 368	Iceland	2, 3, & B4	1	0	2 notches	blue/gold		Hole #14	1	no shims required	-	-	#4	none
50 cl Neviot Mineral Water in Model 440	Israel	2, 3, 5, B4, & B5	1	2 flat black shims	2 notches	blue/gold		Hole #15	1	1 grey shim right	A+	-	#4	none
500 ml PET Water Carbonated & Non-Carbonated Plastic Bottle in Model 360	Italy	2, 3, & B5	1	0	2 notches	blue/gold		Hole #15	NA	NA	NA	NA	NA	none
500 ml PET Contour Coke Bottle in Models 180, 276, 360, 368, & 414	Spain and Italy	2, 3, & B5	1	no shims required	2 notches	blue/gold		Hole #17	1	no shims required	-	-	#4	none
355 ml PET "Pureza Aga" Water Bottle in Models 440 & 368	Mexico	2, 3, 5, & B5	1	6 flat black shims	2 notches	blue/gold		Hole #12	1	0	A+	-	#4	none
500 ml PET Contour Coke Bottle in Model 440	Norway	2, 3, 5, & B6	1	2 flat black & 2 flat grey shims	2 notches	blue/gold		Hole #17	1	0	-	-	#4	none
500 ml Coca Cola "Contour" Plastic Bottle in Models 276 & 360	United Kingdom	2, 3, 5, & B6	1	w/a right & left shim	2 notches	blue/gold		Hole #17	1	1 grey shim right	-	-	#4	none
17 oz. Vittel Water Bottle in Model 276	United Kingdom	2, 3, & B6	0	WILL NOT VEND	-	-		Hole #12	1	no shims required	-	-	#4	none
12 oz. Avalon Spring Water & 12 oz Naya Spring Water Plastic Bottle in Models 368 & 440	United States Canada	2, 3, 5, & B7	1	4 flat black shims	2 notches	blue/gold		Hole #10	1	0	A+	-	#4	none
12 oz. Avalon Spring Water Plastic Bottle In Models 168 & 276	United States	2, 3, 5, 7, & B6	1	4 flat black shims	2 notches	blue/gold		Hole #12	1	no shims required	A+	C+	#4	none

Wide Columns	All Columns	Narrow Columns

										•			
PACKAGE DESCRIPTION & VENDERS APPROVED	COUNTRY	SEE PAGE(S)	LOADING DEPTH	PARTS PER COLUMN	CAM	CAM(S) REQUIRED	REAR SPACER LOCATION	LOADING DEPTH	PARTS REQ'D PER COLUMN	ROD IN	ROD IN	CAM SETTING	OTHER PARTS
	COUNTRY	PAGE(S)	DEFIN	COLUMIN	SETTING		LOCATION	DEFIN	PER COLUMN	1111	IIN	SETTING	PARIS
16.9 oz. Avalon Spring Water Sport Cap In Models 168 & 276	United States	2, 3, 5, & B7	1	2 flat black shims	2 notches	blue/gold	Hole #16	1	no shims required 1 hole plug	-	-	#4	none
16 oz. PET Balsams Spring Water Bottle in Model 368	United States	2, 3, 5, B7, & B8	1	4 flat black shims	2 notches	blue/gold	Hole #12	1	1 grey shim right	front A+ Rear B+	-	#4	none
12 oz Castle Springs & 12 oz Poland Spring Water Plastic Bottle in Models 368 & 440	United States	2, 3, 4, 5, & B8	1	6 flat black shims	2 notches	blue/gold	Hole #12	1	0	A+	-	#4	none
16.9 oz Mountain Valley Spring, 16.9 oz PET Castle Springs, 16.9 oz. PET Poland Spring Water Bottle in Model 368	United States	2, 3, 4, 5, & B8	1	2 flat black shims	2 notches	blue/gold	Hole #15	1	0	В	-	#4	none
20 oz. PET Contour Coke Bottle in model 180	United States	2, 3, 8, & B8	1	1 oscillator milled	2 notches	blue/gold	Hole #17	NA	NA	NA	NA	NA	extended discharge member
16 oz. PET Crystal Light Bottle in Model 368	United States	2, 3, 5, & B9	1	2 flat black shims	2 notches	blue/gold	Hole #14	1	0	В	-	#4	none
330 ml (11.2 oz) Evian Water Bottle in all Models	United States	2, 3, 5, 7, & B9	1	1 right & left column wall	2 notches	blue/gold	Hole #10	1	1 grey shim right	В	-	#4	none
330 ml PET Evian "On Ice" Water Bottle in Model 360	United States	2, 3, 4, & B9	1	6 flat black shims	2 notches	blue/gold	Hole #11	NA	NA	NA	NA	NA	none
500 ml PET Evian "On Ice" Water Bottle in Models 360 & 368	United States	2, 4, & B9	1	4 flat black shims	2 notches	blue/gold	Hole #16	1	0	-	-	#4	none
16.9 oz. PET Evian Water Bottle in Models 360 & 368	United States	2, 4, 5, & B10	1	8 flat black shims	2 notches	blue/gold	Hole #16	1	1 grey shim right	В	-	#4	none
16 oz. PET Glen Falls Water Bottle in Models 276, 300, 368 & 440	United States	2, 4, 5, & B10	1	4 flat black shims	2 notches	blue/gold	Hole #15	1	1 grey shim right	В	-	#4	divider angle
16.9 oz. PET Grayson Water Bottle in models 368 & 440	United States	2, 4, 5, & B10	1	4 flat black shims	2 notches	blue/gold	Hole #17	1	1 grey shim right 1 hole plug rear spacer	В	-	#4	none

NA = Not Applicable @, +, and \* see page 5.

Wide Columns All Columns Narrow Columns

PACKAGE DESCRIPTION	COLIMEDA	SEE	LOADING	PARTS PER	CAM	CAM(S)	REAR SPACER	LOADING	PARTS REQ'D	ROD	ROD	CAM	OTHER
& VENDERS APPROVED	COUNTRY	PAGE(S)	DEPTH	COLUMN	SETTING	REQUIRED	LOCATION	DEPTH	PER COLUMN	IN	IN	SETTING	PARTS
16.9 oz PET LaCroix Water Bottle In Models 360 & 368	United States	2, 3, 4, & B11	1	2 flat black shims	2 notches	blue/gold	Hole #15	1	0	В	-	#4	none
20 oz. Mistic Sport Bottle in Models 414 & 440	United States	2, 4, & B11	1	1 oscillator milled	2 notches	blue/gold	Hole #17	1	1 rear spacer hole plug	ı	-	#4	none
12 oz. Mountain Valley Spring Water Plastic Bottle In Models 368 & 440	United States	2, 3, 5, & B8	1	6 flat black shims	2 notches	blue/gold	Hole #12	1	0	B+	-	#4	none
16.9 oz. (500 ml) Naya Water Plastic Bottle In Models 168 & 276	United States	2, 4, 5, & B11	1	4 flat black shims	2 notches	blue/gold	Hole #16	1	no shims	В	-	#4	none
12 oz. PET Pepsi Bottle in Model 440	United States	2,4, B11 & B12	1	no shims required	2 notches	blue/gold	Hole #10	1	no shims required	ī	-	#4	none
20 oz. PET Pepsi "Fast Break" Bottle in Model 368	Birmingham, AL	2, 4, & B12	1	no shims required	2 notches	blue/gold	Hole #18	1	no shims required	i	-	#4	none
490 ml Poland Spring Water Plastic Bottle in Models 368 & 440	United States	2, 4, 5, & B12	1	2 flat black shims	2 notches	blue/gold	Hole 15	1	1 grey shim right	A+	-	#4	none
16.9 oz. Zephyrhills Spring Water Bottle in Model 440	United States	2, 4, 5, & B12	1	2 flat black shims	2 notches	blue/gold	Hole 15	1	0	В	-	#4	none

### INDIVIDUAL COLUMN SET-UP & SHIMMING

#### 500 ml PET Straight Bottle (East Africa) (In models 368 & 440)

Wide Column Set-Up 1 deep

4 - 801,804,96x.x1 flat black shim (2 each side)

1 - 801,806,39x.x1 cam, blue vending 1 - 801,806,40x.x1 cam, gold adjustable

Cam setting #1 or 2 notches. Rear spacer set in hole #16.

#### Narrow Column Set-Up 1 deep

No shims required.

1 - 267,012,30x.x3 rod and spring assembly

Place rod in hole "B" of rotor. Cam setting #4 or 1 notch.

Rear spacer set in hole #16.

SET DISCHARGE MEMBER AND CLOSURE STRIP FOR BOTTLES.

#### 500 ml PET Contour Coke Bottle (Australia) (In models 276, 360, & 440)

Wide Column Set-Up 1 deep

1 - 801,806,39x.x1 cam, blue vending 1 - 801,806,40x.x1 cam, gold adjustable 2 - 267,070,46x.x3 440 hem channel wide 2 - 267,070,48x.x3 440 hem angle left 440 hem angle right 2 - 267,070,47x.x3 276 hem channel wide 1 - 270,070,17x.x3 2 - 270,070,19x.x3 276 hem angle left 2 - 270,070,18x.x3 276 hem angle right 360 hem channel wide 5 - 270,070,17x.x3 1 - 270,070,19x.x3 360 hem angle left 1 - 270,070,18x.x3 360 hem angle right

Cam setting #1 or 2 notches. Rear spacer set in hole #16.

#### Narrow Column Set-Up 1 deep

1 - 801,805,12x.x1 flat grey shim, right

Cam setting #4 or 1 notch. Rear spacer set in hole #16.

SET DISCHARGE MEMBER AND CLOSURE STRIP FOR BOTTLES.

# 600 ml PET Coca-Cola Contour Bottle (Australia) (In model 440) 600 ml PET Multi-Brand Bottle (Australia) (In models 414 and 440) 600 ml PET Sprite Bottle (Australia) (In model 440)

Wide Column Set-Up

Will not vend at this time.

#### Narrow Column Set-Up

No shims required.

1 - 801,201,53x.x1 milled rotor, 20 oz.

Cam setting #4 or 1 notch. Rear spacer set in hole #18.

#### .5 Liter PET Jeema Water (Australia) (In model 440)

Wide Column Set-Up 1 deep

2 - 801,804,96x.x1 flat black shim (1 each side)

1 - 801,806,39x.x1 cam, blue vending 1 - 801,806,40x.x1 cam, gold adjustable

Cam setting #1 or 2 notches. Rear spacer set in hole #15.

Narrow Column Set-Up 1 deep

No shims required.

1 - 236,010,01x.x3 divider angle (1 per vender)

Cam setting #4 or 1 notch. Rear spacer set in hole #15.

SET DISCHARGE MEMBER AND CLOSURE STRIP FOR BOTTLES.

#### 500 ml PET Mt. Franklin Bottle (Australia) (In models 276, 368, & 440)

Wide Column Set-Up 1 deep

1 - 491,072,70x.x3 milled oscillator assy.,  $1\frac{1}{4}$ " deeper

1 - 801,806,39x.x1 cam, blue vending 1 - 801,806,40x.x1 cam, gold adjustable

No shims required.

Cam setting #1 or 2 notches. Rear spacer set in hole #12.

Narrow Column Set-Up 1 deep

No shims required.

Cam setting #4 or 1 notch.

Rear spacer set in hole #12.

SET DISCHARGE MEMBER AND CLOSURE STRIP FOR BOTTLES.

#### 500 ml PET Pepsi "Wide Mouth" (The Slam) (Australia) (In model 368)

Wide Column Set-Up 1 deep

1 - 801,806,39x.x1 cam, blue vending 1 - 801,806,40x.x1 cam, gold adjustable

No shims required.

Cam setting #1 or 2 notches. Rear spacer set in hole #17.

Narrow Column Set-Up 1 deep

No shims required.

Cam setting #4 or 1 notch.

Rear spacer set in hole #17.

SET DISCHARGE MEMBER AND CLOSURE STRIP FOR BOTTLES.

#### 500 ml PET Powerade Bottle (Australia) (In models 368 & 440)

Wide Column Set-Up 1 deep

1 - 491,072,70x.x3 milled oscillator assy., 1-1/4" deeper

1 - 801,806,39x.x1 cam, blue vending 1 - 801,806,40x.x1 cam, gold adjustable

No shims required.

Cam setting #1 or 2 notches. Rear spacer set in hole #13.

#### 500 ml PET Powerade Bottle (Australia) (In models 368 & 440)

Continued

Narrow Column Set-Up 1 deep

No shims required.

1 - 801,201,50x.x1 milled rotor, 1-1/4" deeper shimless

Cams setting #4 or 1 notch. Rear spacer set in hole #13.

SET DISCHARGE MEMBER AND CLOSURE STRIP FOR BOTTLES.

#### 500 ml PET Straight Bottle (Australia) (In models 276 and 440)

Wide Column Set-Up 1 deep

1 - 443,010,60x.x3 w/a left bottle shim -2 1 - 443,010,70x.x3 w/a right bottle shim -2 1 - 801,806,39x.x1 cam, blue vending 1 - 801,806,40x.x1 cam, gold adjustable

Cam setting #1 or 2 notches. Rear spacer set in hole #15.

#### Narrow Column Set-Up 1 deep

1 - 443,013,90x.x3 440 w/a wall, right 1 - 443,013,80x.x3 276 w/a wall, right 1 - 267,012,30x.x3 rod and spring assembly 1 - 236,010,01x.x3 divider angle

Place rod in hole "C" in front and hole "A" in rear of rotor.

Cam setting #4 or 1 notch. Rear spacer set in hole #15.

SET DISCHARGE MEMBER AND CLOSURE STRIP FOR BOTTLES.

#### 16.9 oz PET Naya Water Bottle (Canada) (In model 440)

#### 16.9 oz PET Avalon Water Bottle (United States) (In models 440 & 368)

Wide Column Set-Up 1 deep

4 - 801,804,96x.x1 flat black shim (2 each side) 1 - 801,806,39x.x1 cam, blue vending

1 - 801,806,40x.x1 cam, gold adjustable

Cam setting #1 or 2 notches. Rear spacer set in hole #16.

#### Narrow Column Set-Up 1 deep

1 - 801,805,12x.x1 flat grey shim, right 1 - 267,012,30x.x3 rod and spring assy.

Place rod in hole "B" of rotor. Cam setting #4 or 1 notch. Rear spacer set in hole #16.

SET DISCHARGE MEMBER AND CLOSURE STRIP FOR BOTTLES.

#### 50 cl Contrex Water Plastic Bottle (France) (In model 368)

Wide Column Set-Up 1 deep

2 - 801,804,96x.x1 flat black shim (1 each side)

1 - 801,806,39x.x1 cam, blue vending 1 - 801,806,40x.x1 cam, gold adjustable

Cam setting #1 or 2 notches. Rear spacer set in hole #16.

#### 50 cl Contrex Water Plastic Bottle (France) (In model 368)

Narrow Column Set-Up 1 deep

1 - 801,805,12x.x1 flat grey shim, right 1 - 267,012,30x.x3 rod and spring assembly

1 - 901,902,00x.x1 red tubing

Place rod with red tube in hole "A" of rotor.

Cam setting #4 or 1 notch. Rear spacer set in hole # 16.

#### 50 cl PET Evian Water (France) (In model 368)

Wide Column Set-Up 1 deep

4 - 801,804,96x.x1 flat black shim (2 each side)

1 - 801,806,39x.x1 cam, blue vending 1 - 801,806,40x.x1 cam, gold adjustable

Cam setting #1 or 2 notches. Rear spacer set in hole #16.

#### Narrow Column Set-Up 1 deep

1 - 801,805,12x.x1 flat grey shim, right 1 - 267,012,30x.x3 rod and spring assembly

Place rod in hole "B" of rotor. Cam setting #4 or 1 notch. Rear spacer set in hole #16.

SET DISCHARGE MEMBER AND CLOSURE STRIP FOR BOTTLES.

#### 500 ml PET Bottle (Iceland) (In models 360 & 368)

Wide Column Set-Up 1 deep

No shims required.

1 - 801,806,39x.x1 cam, blue vending 1 - 801,806,40x.x1 cam, gold adjustable

Cam setting #1 or 2 notches. Rear spacer set in hole #14.

#### Narrow Column Set-Up 1 deep

No shims required.

Cam setting #4 or 1 notch.

Rear spacer set in hole #14.

SET DISCHARGE MEMBER AND CLOSURE STRIP FOR BOTTLES

#### 50 cl PET Neviot Mineral Water Plastic Bottle (Israel) (In model 440)

Wide Column Set-Up 1 deep

2 - 801,804,96x.x1 flat black shim (1 each side)

1 - 801,806,39x.x1 cam, blue vending 1 - 801,806,40x.x1 cam, gold adjustable

Cam setting #1 or 2 notches. Rear spacer set in hole #15.

#### Narrow Column Set-Up 1 deep

1 - 801,805,12x.x1 flat grey shim, right 1 - 267,012,30x.x3 rod & spring assembly

1 - 901,902,00x.x1 red tubing

Place rod with red tubing in hole "A" of rotor.

Cam setting #4 or 1 notch. Rear spacer set in hole #15.

SET DISCHARGE MEMBER AND CLOSURE STRIP FOR BOTTLES.

Continued

# 500 ml PET Water Carbonated Plastic Bottle (Italy) (In model 360) 500 ml PET Water Non-Carbonated Plastic Bottle (Italy) (In model 360)

Wide Column Set-Up 1 deep

No shims required.

1 - 801,806,39x.x1 cam, blue vending 1 - 801,806,40x.x1 cam, gold adjustable

Cam setting #1 or 2 notches. Rear spacer set in hole #15.

SET DISCHARGE MEMBER AND CLOSURE STRIP FOR BOTTLES.

# 500 ml PET Coca-Cola Contour Bottle (Spain) (In models 180, 276, 360, 368, and 414) 500 ml PET Coca-Cola Contour Bottle (Italy) (In models 368, 414, and 440)

Wide Column Set-Up 1 deep

No shims required.

1 - 801,806,39x.x1 cam, blue vending 1 - 801,806,40x.x1 cam, gold adjustable

Cam setting #1 or 2 notches. Rear spacer set in hole #17.

#### Narrow Column Set-Up 1 deep

No shims required.

Cam setting #4 or 1 notch.

Rear spacer set in hole #17.

SET DISCHARGE MEMBER AND CLOSURE STRIP FOR BOTTLES.

#### 355 ml PET Pureza Aga Water Bottle (Mexico) (In models 440 & 368)

Wide Column Set-Up 1 deep

6 - 801,804,96x.x1 flat black shim (3 each side)

1 - 801,806,39x.x1 cam, blue vending 1 - 801,806,40x.x1 cam, gold adjustable

Cam setting #1 or 2 notches. Rear spacer set in hole #12.

#### Narrow Column Set-Up 1 deep

1 - 267,012,30x.x3 rod and spring assembly

1 - 901,902,00x.x1 red tubing

Place rod with red tubing in hole "A" of rotor.

Cam setting #4 or 1 notch.

#### 500 ml PET Contour Coke Bottle (Norway) (In model 440)

Wide Column Set-Up 1 deep

2 - 801,804,96x.x1 flat black shim (1 each side) 2 - 801,805,12x.x1 flat grey shim (1 each side) 1 - 801,806,39x.x1 cam, blue vending

1 - 801,806,39x.x1 cam, blue vending cam, gold adjustable

Cam setting #1 or 2 notches. Rear spacer set in hole #17.

#### Narrow Column Set-Up 1 deep

No shims required.

Cam setting #4 or 1 notch.

Rear spacer set in hole #17.

#### 500 ml Coca-Cola "Contour" Plastic Bottle (United Kingdom) (In model 276 & 360)

Wide Column Set-Up 1 deep

Cam setting #1 or 2 notches. Rear spacer set in hole #17.

Narrow Column Set-Up 1 deep

1 - 801,805,12x.x1 flat grey shim, right

Cam setting #4 or 1 notch. Rear spacer set in hole #17.

SET DISCHARGE MEMBER AND CLOSURE STRIP FOR BOTTLES.

#### 17 oz. PET Vittel (Square) Water Bottle (United Kingdom) (In model 276)

Wide Column Set-Up

Will Not Vend.

Narrow Column Set-Up 1 deep

No shims required.

Cam setting #4 or 1 notch.

Rear spacer set in hole #12.

SET DISCHARGE MEMBER AND CLOSURE STRIP FOR BOTTLES.

#### 12 oz. Avalon Spring Water (7.37"ht. x 2.31"dia.) (United States) (In models 168 & 276)

Wide Column Set-Up 1 deep

4 - 801,804,96x.x1 flat black shim (2 each side)

1 - 801,806,39x.x1 cam, blue vending 1 - 801,806,40x.x1 cam, gold adjustable

Cam setting #1 or 2 notches. Rear spacer set in hole #12.

#### Narrow Column Set-Up 1 deep

No shims required.

2 - 267,012,30x.x3 rod and spring assembly

2 - 901,902,00x.x1 red tubing

Place one rod with red tubing in hole "A" of rotor. Place one rod with red tubing in hole "C" of rotor.

Cam setting #4 or 1 notch.

Rear spacer set in hole #12.

#### 12 oz. Avalon Spring Water Bottle (6.53"ht. x 2.46" dia.) (United States) (In model 440) 12 oz Naya Spring Water Plastic Bottle (Canada) (In models 368 & 440)

Wide Column Set-Up 1 deep

4 - 801,804,96x.x1 flat black shim (2 each side)

cam, blue vending 1 - 801.806.39x.x1 cam, gold adjustable 1 - 801,806,40x.x1

Cam setting #1 or 2 notches. Rear spacer set in hole #10.

#### Narrow Column Set-Up 1 deep

No shims required.

1 - 267,012,30x.x3 rod and spring assembly

1 - 901,902,00x.x1 red tubing

Place rod with red tubing in hole "A" of rotor.

Cam setting #4 or 1 notch. Rear spacer set in hole #10.

#### 16.9 oz. PET Avalon Spring Water Sport Cap Bottle (USA) (In model 168 & 276)

Wide Column Set-Up 1 deep

2 - 801,804,96x.x1 flat black shim (1 each side)

1 - 801,806,39x.x1 cam, blue vending 1 - 801,806,40x.x1 cam, gold adjustable

Cam setting #1 or 2 notches. Rear spacer set in hole #16.

#### Narrow Column Set-Up 1 deep

No shims required.

1 - 801,903,04x.x1 hole plug

Cam setting #4 or 1 notch. Rear spacers set for bottles.

SET DISCHARGE MEMBER AND CLOSURE STRIP FOR BOTTLES.

#### 16 oz. PET Balsams Spring Water (United States) (In model 368)

Wide Column Set-Up 1 deep

4 - 801,804,96x.x1 flat black shim (2 each side)

1 - 801.806.39x.x1 cam, blue vending 1 - 801,806,40x.x1 cam, gold adjustable

Cam setting #1 or 2 notches. Rear spacer set in hole #12.

#### Narrow Column Set-Up 1 deep

1 - 801,805,12x.x1 flat grey shim, right 1 - 267,012,30x.x3 rod & spring assembly

1 - 901,902,00x.x1 red tubing

Place rod with red tubing in hole "A" front and hole "B" rear of rotor.

Cam setting #4 or 1 notch. Rear spacer set in hole #12.

#### 12 oz Mountain Valley Spring Water Plastic Bottle (United States) (In models 368 & 440)

12 oz Poland Spring Water Plastic Bottle (United States) (In models 368 & 440)

#### 12 oz Castle Springs Water Plastic Bottle (United States) (In models 368 & 440)

Wide Column Set-Up 1 deep

6 - 801,804,96x.x1 flat black shim (3 each side)

1 - 801,806,39x.x1 cam, blue vending 1 - 801,806,40x.x1 cam, gold adjustable

Cam setting #1 or 2 notches. Rear spacer set in hole #12.

#### Narrow Column Set-Up 1 deep

No shims required.

1 - 267,012,30x.x3 rod and spring assembly

1 - 901,902,00x.x1 red tubing

Place one rod with red tubing in hole "A" of rotor for Poland Spring & Castle Springs bottles.

Place one rod with red tubing in hole "B" of rotor for Mountain Valley Spring bottle.

Cam setting #4 or 1 notch. Rear spacer set in hole #12.

#### 16.9 oz. Mountain Valley Spring Water Bottle (United States) (In model 368)

#### 16.9 oz. PET Castle Springs Water Bottle (United States) (In models 368 & 440)

#### 16.9 oz. PET Poland Spring Water (United States) (In model 368)

Wide Column Set-Up 1 deep

2 - 801,804,96x.x1 flat black shim (1 each side)

1 - 801,806,39x.x1 cam, blue vending 1 - 801,806,40x.x1 cam, gold adjustable

Cam setting #1 or 2 notches. Rear spacer set in hole #15.

#### Narrow Column Set-Up 1 deep

1 - 267,012,30x.x3 rod & spring assembly

Place rod in hole "B" of rotor.

Cam setting #4 or 1 notch.

Rear spacer set in hole #15.

SET DISCHARGE MEMBER AND CLOSURE STRIP FOR BOTTLES.

#### 20 oz. PET Coca-Cola "Contour" Bottle (United States) (In model 180)

Wide Column Set-Up 1 deep

No shims required.

1 - 491,075,20x.x3 milled oscillator, 20 oz. 1 - 801,806,39x.x1 cam, blue vending 1 - 801,806,40x.x1 cam, gold adjustable

1 - see list below extended discharge member (1 per vender)

491,051,70x.x4 for Wide Coke Circular and Generic Circular venders

491,051,90x.x4 for Full Length Sign and Display venders

Cam setting #1 or 2 notches.

Rear spacer set in hole #17.

SET CLOSURE STRIP FOR BOTTLES.

#### 16 oz. PET Crystal Light Bottle (United States) (In model 368)

Wide Column Set-Up 1 deep

2 - 801,804,96x.x1 flat black shim (1 each side)

1 - 801,806,39x.x1 cam, blue vending 1 - 801,806,40x.x1 cam, gold adjustable

Cam setting #1 or 2 notches. Rear spacer set in hole #14.

Narrow Column Set-Up 1 deep

1 - 267,012,30x.x3 rod and spring assembly

Place rod in hole "B" of rotor. Cam setting #4 or 1 notch. Rear spacer set in hole #14.

SET DISCHARGE MEMBER AND CLOSURE STRIP FOR BOTTLES.

#### 330 ml (11.2 oz.) PET Evian Water Bottle (United States) (In all models)

Wide Column Set-Up 1 deep

 $\begin{array}{ccc} \text{1 -} & \text{reference list} & \text{w/a column wall left} \\ & 443,011,50x.x3 & 440,414 \end{array}$ 

443,011,30x.x3 276, 348, 360, 368

445,010,80x.x3 180

1 - reference list w/a column wall right

443,011,60x.x3 440, 414

443,011,40x.x3 276, 348, 360, 368

445,010,90x.x3 180 Cam setting #1 or 2 notches. Rear spacer set in hole #10.

Narrow Column Set-Up 1 deep

1 - 801,805,12x.x1 flat grey shim, right 1 - 267,012,30x.x3 rod and spring assembly

Place rod in hole "B" of rotor. Cam setting #4 or 1 notch. Rear spacer set in hole #10.

#### 330 ml PET Evian "On Ice" Water Plastic Bottle (United States) (In model 360)

Wide Column Set-Up

6 - 801,804,96x.x1 flat black shim (3 each side)

1 - 801,806,39x.x1 cam, blue vending 1 - 801,806,40x.x1 cam, gold adjustable

Cam setting #1 or 2 notches. Rear spacer set in hole #11.

SET DISCHARGE MEMBER AND CLOSURE STRIP FOR BOTTLES.

#### 500 ml PET Evian "On Ice" Water Bottle (United States) (In models 360 & 368)

Wide Column Set-Up 1 deep

4 - 801,804,96x.x1 flat black shim (2 each side)

1 - 801,806,39x.x1 cam, blue vending 1 - 801,806,40x.x1 cam, gold adjustable

Cam setting #1 or 2 notches. Rear spacer set in hole #16.

Narrow Column Set-Up 1 deep

No shims required.

Cam setting #4 or 1 notch.

Rear spacer set in hole #16.

#### 16.9 oz. PET Evian Water Bottle (United States) (In models 360 & 368)

Wide Column Set-Up 1 deep

8 - 801,804,96x.x1 flat black shim (4 each side)

1 - 801,806,39x.x1 cam, blue vending 1 - 801,806,40x.x1 cam, gold adjustable

Cam setting #1 or 2 notches. Rear spacer set in hole #16.

#### Narrow Column Set-Up 1 deep

1 - 801,805,12x.x1 flat grey shim, right 1 - 267,012,70x.x3 rod & spring assembly

Install rod in hole "B" of rotor. Cam setting #4 or 1 notch. Rear spacer set in hole #16.

SET DISCHARGE MEMBER AND CLOSURE STRIP FOR BOTTLES.

#### 16 oz. PET Glen Falls Water Bottle (United States) (In models 276, 300, 368, & 440)

Wide Column Set-Up 1 deep

4 - 801,804,96x.x1 flat black shim (2 each side)

1 - 801,806,39x.x1 cam, blue vending 1 - 801,806,40x.x1 cam, gold adjustable

Cam setting #1 or 2 notches. Rear spacer set in hole #15.

#### Narrow Column Set-Up 1 deep

1 - 801,805,12x.x1 flat grey shim, right 1 - 267,012,30x.x3 rod & spring assembly 1 - 236,010,01x.x3 divider angle (1 per vender)

Place rod in hole "B" of rotor. Cam setting #4 or 1 notch. Rear spacer set in hole #15.

SET DISCHARGE MEMBER AND CLOSURE STRIP FOR BOTTLES.

#### 16.9 oz. PET Grayson Water Bottle (United States) (In models 368 & 440)

Wide Column Set-Up 1 deep

4 - 801,804,96x.x1 flat black shim (2 each side)

1 - 801,806,39x.x1 cam, blue vending 1 - 801,806,40x.x1 cam, gold adjustable

Cam setting #1 or 2 notches. Rear spacer set in hole #15.

#### Narrow Column Set-Up 1 deep

1 - 801,805,12x.x1 flat grey shim, right 1 - 267,012,30x.x3 rod & spring assembly

1 - 801,903,04x.x1 hole plug, rear spacer bottom hole

Install the rod in hole "B" of the rotor.

Cam setting #4 or 1 notch. Rear spacer set in hole #15.

#### 16.9 oz PET LaCroix Water Bottle (United States) (In models 360 & 368)

Wide Column Set-Up 1 deep

2 - 801,804,96x.x1 flat black shim (1 each side)

1 - 801,806,39x.x1 cam, blue vending 1 - 801,806,40x.x1 cam, gold adjustable

Cam setting #1 or 2 notches. Rear spacer set in hole #15.

Narrow Column Set-Up 1 deep

1 - 267,012,30x.x3 rod and spring assy.

Install the rod in hole "B" of the rotor.

Cam setting #4 or 1 notch. Rear spacer set in hole #15.

SET DISCHARGE MEMBER AND CLOSURE STRIP FOR BOTTLES.

#### 16.9 oz. (500 ml) PET Naya Water Bottle (United States & Canada) (168 & 276)

Wide Column Set-Up 1 deep

4 - 801,804,96x.x1 flat black shim (2 each side)

1 - 801,806,39x.x1 cam, blue vending 1 - 801,806,40x.x1 cam, gold adjustable

Cam setting #1 or 2 notches. Rear spacer set in hole #16.

Narrow Column Set-Up 1 deep

No shims required.

1 - 267,012,30x.x3 rod and spring assy.

Place one rod in hole "B" of rotor.

Cam setting #4 or 1 notch.

Rear spacer set in hole #16.

SET DISCHARGE MEMBER AND CLOSURE STRIP FOR BOTTLES.

#### 20 oz. PET Mistic Sport Bottle (United States) (In models 414 & 440)

Wide Column Set-Up 1 deep

No shims required.

1 - 491,075,20x.x3 milled oscillator, 20 oz. 1 - 801,806,39x.x1 cam, blue vending 1 - 801,806,40x.x1 cam, gold adjustable

Cam setting #1 or 2 notches. Rear spacer set in hole #17.

Narrow Column Set-Up 1 deep

No shims required.

1 - 801,903,04x.x1 hole plug, rear spacer Install hole plug in lower hole of rear spacer.

Cam setting #4 or 1 notch.

Rear spacer set in hole #17.

#### 12 oz. PET Pepsi Bottle (4 section bottom) (United States) (In model 440)

Wide Column Set-Up 1 deep

No shims required.

1 - 801,806,39x.x1 cam, blue vending 1 - 801,806,40x.x1 cam, gold adjustable

Cam setting #1 or 2 notches. Rear spacer set in hole #10.

#### Narrow Column Set-Up 1 deep

No shims required.

Cam setting #4 or 1 notch.

Rear spacer set in hole #10.

#### 20 oz. PET Pepsi "Fast Break" Bottle (Birmingham, AL) (In model 368)

Wide Column Set-Up 1 deep

1 - 801,806,39x.x1 cam, blue vending 1 - 801,806,40x.x1 cam, gold adjustable

No shims required.

Cam setting #1 or 2 notches. Rear spacer set in hole #18.

#### Narrow Column Set-Up 1 deep

Cam setting #4 or 1 notch.

Rear spacer set in hole #18.

SET DISCHARGE MEMBER AND CLOSURE STRIP FOR BOTTLES.

#### 490 ml Poland Spring Water Plastic Bottle (In models 368 & 440)

Wide Column Set-Up 1 deep

2 - 801,804,96x.x1 flat black shim (1 each side)

1 - 801,806,39x.x1 cam, blue vending 1 - 801,806,40x.x1 cam, gold adjustable

Cam setting #1 or 2 notches. Rear spacer set in hole #15.

#### Narrow Column Set-Up 1 deep

1 - 801,805,12x.x1 flat grey shim, right 1 - 267,012,30x.x3 rod & spring assembly

1 - 901,902,00x.x1 red tubing

Place one rod with red tubing in hole "A" of rotor.

Cam setting #4 or 1 notch. Rear spacer set in hole #15.

SET DISCHARGE MEMBER AND CLOSURE STRIP FOR BOTTLES.

#### 16.9 oz PET Zephyrhills Spring Water Bottle (United States) (In model 440)

Wide Column Set-Up 1 deep

2 - 801,804,96x.x1 flat black shim (1 each side)

1 - 801,806,39x.x1 cam, blue vending 1 - 801,806,40x.x1 cam, gold adjustable

Cam setting #1 or 2 notches. Rear spacer set in hole #15.

#### Narrow Column Set-Up 1 deep

1 - 267,012,30x.x3 rod and spring assembly

Place rod in hole "B" of rotor.

Cam setting #4 or 1 notch.

Rear spacer set in hole #15.